



NAC3MPB-1

Discontinued

Successor product: NAC3MPXXB

Chassis connector, power-out, 3/16" flat tab terminals, grey

The powerCON is a locking 3 conductor equipment AC connector with contacts for line, neutral and pre-mating ground contact. It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed in order to guarantee a safe power connection.

Attention: The powerCON is a connector without breaking capacity, i.e. the powerCON should not be connected or disconnected under load or live!

Features & Benefits

- | | |
|---|---|
| <ul style="list-style-type: none">• Locking 20 A / 250 V ac appliance coupler | <ul style="list-style-type: none">• 3 contacts for line, neutral and pre-mating safety ground |
| <ul style="list-style-type: none">• Power-in (blue) and power-out (grey) versions with different keying to avoid the possibility of intermating | <ul style="list-style-type: none">• Fast and easy twist lock latching system |
| <ul style="list-style-type: none">• Extremely robust and reliable | <ul style="list-style-type: none">• Ergonomic design |
| <ul style="list-style-type: none">• User friendly latch design for easy handling | <ul style="list-style-type: none">• UL, cUL recognized components
VDE certified |
| <ul style="list-style-type: none">• Branded with unique hologram - guarantees genuine and authentic Neutrik product | |

Technical Information

Product	
Title	NAC3MPB-1
Gender	male

Electrical	
Contact resistance	$\leq 3 \text{ m}\Omega$
Dielectric strength	4 kVdc / 2.8 kVac
Insulation resistance	$> 0.1 \text{ G}\Omega$ (after damp heat test IEC 68-2-30)
Number of electrical contacts	2 + PE
Rating Europe	EN 61984:20 A 250 V AC
Rating USA	UL 1977:20 A 250 V AC

Mechanical	
Lifetime	> 1000 mating cycles
Wiresize	2.5mm ²
	12 AWG
Locking device	Quick Lock
Mounting direction	Front mounting
Chassis shape	D

Material	
Contact plating	2 µm Ag
Locking element	Steel Ck67
Shell	Polyamide (PA 6.6 30 % GR)
Contacts	Bronze (CuNi1Si0.2)

Environmental	
Flammability	UL 94 V-0
Protection class	IP 20
Temperature range	-30 °C to +80 °C