



## NADB15MF-B

15 pole D-SUB feedthrough, male to female, black  
D-shape housing

### Features & Benefits

- Ideal for audio networking and integration of equipment into video systems

Technical Information

| Product |            |
|---------|------------|
| Title   | NADB15MF-B |
| Gender  | male       |

| Electrical                      |            |
|---------------------------------|------------|
| Contact resistance              | 30 mΩ      |
| Insulation resistance           | > 5 GΩ     |
| Number of electronical contacts | 15         |
| Rated current per contact       | 3 A        |
| Rated voltage                   | 50 V ac    |
| Dielectric strength             | > 0.5 kVac |

| Mechanical         |                |
|--------------------|----------------|
| Panel thickness    | 4 mm           |
| Wiresize           |                |
| Wiring             | Feedthrough    |
| Mounting direction | Front mounting |
| Chassis shape      | D              |

| Material        |                         |
|-----------------|-------------------------|
| Contact plating | Au                      |
| Contacts        | Brass (Pb-free)         |
| Insert          | Steel , tin plated, PBT |
| Shell           | Zinc diecast (ZnAl4Cu1) |
| Shell plating   | Black chromium          |

| Environmental     |                  |
|-------------------|------------------|
| Flammability      | UL 94-V0         |
| Temperature range | -25 °C to +85 °C |