



## NE8FDP-SE

RJ45 feedthrough receptacle, combined with sealing kit SE8FD, D-shape metal flange with the latch lock, mounting screws included

The etherCON Series is a ruggedized and lockable RJ45 connector system, optimized for pro audio, video and lightning network applications. The chassis connectors are shaped to fit into standardized panels out of the entertainment industry.

The D-Series offers the most rugged design of the etherCON series and is perfectly suitable for panel mount and the installer market.

Attention! Does not intermate with CAT6 cable connector NE8MC6-MO and NKE6S\* cables.

## Features & Benefits

- |  |   |
|--|---|
| <ul style="list-style-type: none"><li>• In combination with NE8MC-1 waterproof according to IP54</li></ul> | <ul style="list-style-type: none"><li>• Accommodates NE8MC* or any standard RJ45 plug</li></ul> |
| <ul style="list-style-type: none"><li>• Approved latch lock system</li></ul>                               | <ul style="list-style-type: none"><li>• Mountable from the front or rear of the panel</li></ul> |
| <ul style="list-style-type: none"><li>• CAT5e according to ISO/IEC 11801 and TIA/EIA 568A/B</li></ul>      | <ul style="list-style-type: none"><li>• PoE type 4 class 8 (100W) acc. IEEE 802.3bt</li></ul>   |

Technical Information

Product	
Title	NE8FDP-SE
Type	Chassis
Connection Type	etherCON
Gender	female

Electrical	
Contact resistance	< 50 mΩ
Dielectric strength	1 kVdc
Frequencyrange	1 - 100 MHz
Insulation resistance	> 0.5 GΩ
Rated current per contact	1.5 A
Rated voltage	≤ 57 V
Transmission performance	CAT5e acc. to TIA/EIA 568A/B component specifications CAT5e acc. to ISO/IEC 11801 component specifications
Power over Ethernet	PoE type 4 class 8 (100W) acc. IEEE 802.3bt

**Mechanical**

Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	1000 mating cycles
Panel thickness	2 mm - 4 mm , 0.08" - 0.16"
Wiresize	
Wiring	Feedthrough
Locking device	Latch lock
Chassis shape	D

**Material**

Contact plating	0.2 µm Au over Ni plating
Contacts	Bronze (CuSn8)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Chromium

**Environmental**

Flammability	UL 94 V-0
Standard compliance	TIA/EIA 586B, IEC11801
Temperature range	-30 °C to +80 °C
Standard compliance	ISO/IEC 11801-1 Ed. 1.0 (2017-11) IEC 60603-7-3 Ed.2.0 (2010-04) IEC 60512-99-002 Ed.2.0 (2022-01) IEC 60512-9-3 (2011-06)