



NC5FX1-TOP

5-poliger Kabelstecker, TRUE OUTDOOR PROTECTION (TOP), vergoldete Kontakte.

Geschützt nach IP65 für Aussenanwendungen in gestecktem Zustand mit entsprechendem Gegenstecker/Buchse der XLT-TOP Serie.

Features & Benefits

- Abgedichteter XLR-Stecker für den Einsatz in rauen Umgebungen mit höchsten Anforderungen.
- Schlagfestes UV-beständiges Material
- Schutzklasse IP65
- Erfüllt TOP Anforderungen in Anlehnung an UL50E

Technische Informationen

Produkte	
Title	NC5FX1-TOP
Connection Type	XLR
Gender	female

Elektrisch	
Capacitance between contacts	$\leq 4 \text{ pF}$
Contact resistance	$\leq 3 \text{ m}\Omega$
Dielectric strength	1,5 kVdc
Insulation resistance	$> 10 \text{ G}\Omega$ (initial)
Rated current per contact	16 A
Rated voltage	$< 50 \text{ V}$

Mechanische Daten	
Cable O.D.	5.0 - 8.0 mm
Insertion force	$\leq 20 \text{ N}$
Withdrawal force	$\leq 20 \text{ N}$
Lifetime	> 1000 mating cycles
Wiresize	max. 1.0 mm^2
Wiresize	max. 18 AWG
Wiring	Solder contacts
Locking device	Latch lock

Material	
Bushing	UV-resistant rubber
Contact plating	Gold (Au) over Nickel (Ni)
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 6.6 30 % GR)
Locking element	St3K32 (latch) / Ck 67 (spring)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Nickel
Strain relief	Polyacetal
Sealing jacket	UV-resistant rubber

Umwelt	
Approvals	UL
Flammability	UL 94 HB
Standard compliance	IEC 61076-2-103
Protection class	IP65, UL50E enclosure type 4 (mated)
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C