

CP-PM

CONNEX cPot Einbaustecker



Ausführungen

Artikel	Beschreibung	Bestellnr.
CP-PMA	Einbaustecker PE axial 10-25 mm² IP65	1027373
CP-PMB	Einbaustecker PE terminal block 2x35/1x25 mm² IP65	1027374
CP-PM620	Einbaustcker PE M6x20 mm IP65	1027375

Technical Information

Produkte	
Description	CP-PMx
Scope of delivery	CP-PMA: 1x panel housing male green, 1x insert male yellow, 1x axial contact 10-25mm ² male, 13mm isolation of cable has to be removed
	CP-PMB: Panel male PE terminal block 2x35/1x25 mm ²
	CP-PM620: 1x panel housing male green, 1x insert male yellow, 1x contact male with M6 thread 20mm

Elektrisch	
Contactor resistance	≤0,3 mΩ

Mechanische Daten	
Lifetime	> 500 Mating cycles per connector
Locking device	Latch lock
Conductor cross section	16 mm ² , 25 mm ²

Material	
Contact	1 contact, copper alloy
Shell	Polycarbonat (PC)

Umwelt	
Standards compatibility	UL94-V0 (connector)
Protection class nach IEC 60529	IP65 in mated condition
Temperature range	-40 °C – 55°C

