



NC10FDX-TOP

8+2 pole female chassis connector, TRUE
OUTDOOR PROTECTION (TOP)

The X-TOP series is a "heavy-duty" XLR cable connector for outdoor use. IP65 rated and TOP approved in consideration to UL50E by mating with related cable or chassis connector of the XLR TOP range

Gold contacts are standard.

Features & Benefits

- Heavy-duty sealed XLR connector range for harsh and demanding environment.
- High impact UV-resistant materials.
- Receptacle with duplex ground contact for excellent signal integrity.
- Superior ruggedness compared to RJ45 type connectors.
- IP65 rated and TOP approved in consideration to UL50E by mating with related cable or chassis connector of the XLR TOP range
- D-size housing provides installation compatibility with industry standard D mounting dimensions.
- Suitable for data offering CAT 5e performance and power up to 16 A and 50 V - exceeds PoE+ capabilities.
- IEC 61984 certified

Technical Information

Produkte	
Title	NC10FDX-TOP
Connection type	XLR
Gender	Female

Elektrisch	
Contact resistance	$\leq 3 \text{ m}\Omega$
Dielectric strength	1 kVdc
Insulation resistance	$> 10 \text{ G}\Omega$ (initial)
Number of electrical contacts	8 + 2
Rated current per contact	16 A (power pins), 3 A (data pins)
Rated voltage	50 V
Cable shield - shell connection	choosable
Transmission performance	CAT 5e

Mechanische Daten	
Insertion force	$\leq 20 \text{ N}$
Withdrawal force	$\leq 20 \text{ N}$
Lifetime	> 1000 mating cycles
Wiring	Solder contacts
Wiring Size	$< 2.5 \text{ mm}^2 / < 1 \text{ mm}^2$ (8 x 24 AWG + 2 x 16AWG)
Locking device	Latch lock
Mounting direction	Front mounting
Chassis shape	D

Material	
Contact plating	Au over Ni
Contacts	Brass
Insert	Polyamide
Locking element	Stainless steel
Gasket	TPE
Shell	Polyamide

Umwelt	
Flammability acc. to UL94	V-0
Standard compliance	IEC 61076-2-103
Protection class according to IEC 60529	IP 65
Solderability acc. to	IEC 60068-2-20
Temperature range	-30 °C to +80 °C
Pollution degree acc. to IEC 60664-1	II