



NC3FD-LX-M3-BAG

3 pole female receptacle, solder cups, black housing, silver contacts, M3 mounting holes

The DLX series features a compact all metal housing with an ingenious duplex ground contact, which offers excellent RF protection and shielding. It is the ideal match for mating with Neutrik's EMC XLR cable connector.

Features & Benefits

- All metal housing offers best overall RF protection and electromagnetic shielding
- Duplex ground contact for excellent contact integrity between chassis and cable connector
- Unique cage type female contact on 3 pole version increases conductivity and reduces wear on the mated male contact
- Female contact incorporates a solder barrier to prevent solder running into the contact mating area
- Optional connection to easily join pin1 to chassis ground
- Larger solder contacts for easier termination
- D-style housing provides installation compatibility with industry standard D mounting dimensions

Technische Informationen

Produkte	
Titel	NC3FD-LX-M3-BAG
Verbindungstyp	XLR
Geschlecht	female

Elektrisch	
Kapazität zwischen Kontakten	$\leq 4 \text{ pF}$
Durchgangswiderstand	$\leq 5 \text{ m}\Omega$
Durchschlagsfestigkeit	1,5 kVdc
Isolationswiderstand	$> 10 \text{ G}\Omega$ (initial)
Nennstrom pro Kontakt	16 A
Nennspannung	$< 50 \text{ V}$

Mechanische Daten	
Einsteckkraft	$\leq 20 \text{ N}$
Aussteckkraft	$\leq 20 \text{ N}$
Lebensdauer	> 1000 mating cycles
Leiterquerschnitt	max. 2.5 mm^2
Leiterquerschnitt	max. 14 AWG
Anschlussart	Solder contacts
Verriegelung	Latch lock
Einbaurichtung	Rear mounting
Gehäuseform	D
Mounting	Mounting holes with M3 threads

Material

Kontaktbeschichtung	2 µm Ag
Kontakte	Bronze (CuSn6)
Einsatz	PA66
Verriegelungselement	Steel Ck67
Gehäuse	Zinc diecast (ZnAl4Cu1)
Gehäusebeschichtung	Black chromium

Umwelt

Entflammbarkeit	UL 94 V-0
Normenkompatibilität	IEC 61076-2-103
Schutzklasse	IP 40
Lötbarkeit	Complies with IEC 68-2-20
Temperaturbereich	-30 °C to +80 °C