NL4MPXX-TRUE1

NEUTRIK speakON® TRUE1® expands the TRUE1® platform into professional audio connectivity. Developed for demanding professional audio applications, the 4-pole connector system combines reliable audio signal transmission with secure locking, robust mechanical performance and true outdoor capability.

Features & Benefits

- Ruggedized 4-pole professional audio connection system
- Rated up to 25 A / 250 V
- IP65 protection in all condition
- Airtight chassis design
- 1440 hours salt spray resistance
- UV-resistant materials for demanding outdoor environments
- Proven NEUTRIK speakON® twist-lock mechanism
- Rated lifetime of min. 5'000 mating cycles

Technical Information

Produkte	
Title	NL4MPXX-TRUE1
Product Family	speakON
Connection type	chassis connector
Gender	male

All rights reserved / 20.11.2026

NEUTRIK

Elektrisch	
Contact resistance	≤ 2 mΩ
Dielectric strength	2.8 kVac
Insulation resistance	> 0.1 GΩ
Number of electrical contacts	4
Rating	25A 250VAC
Attention	speakON is NOT to be used as an mains or power supply connector!

Mechanische Daten	
Installation direction	Front mounting
Tightening torque	0.4 Nm - 0.6 Nm
Lifetime	5'000 mating cycles
Termination	3/16" flat tabs (e.g. NLFASTON)
Locking device	Twist lock
Chassis shape	D Size

Material	
Contact plating	Ag
Contacts	Copper Alloy
Locking element	Stainless Steel
Shell	Polyamide (PA 6.6)
Sealing cap	Silicon

All rights reserved / 20.11.2026

Umwelt	
Corrosion resistance	1440 h
Flammability	V0
UV/Ozone resistance	1000h tested
Protection class	in all condition IP65
Operating temperature	-30 °C to +80 °C
REACH	compliant
RoHS	compliant

All rights reserved / 20.11.2026