



opticalCON HYBRID MED Einbausteckverbinder

Female Einbausteckverbinder mit widerstandsfähiger antikorrosiver Beschichtung, 2 Crimp-Kontakte, 1x MPO-Durchgangsbuchse und 1x GND-Kontakt für den Kabelschirm am Gehäuse.

Die Einbauversion fungiert als Durchgangsadapter für eine leichte Installation – rückseitig kann ein MPO-Patch-Kabel angeschlossen werden kann. Der Frontplattenausschnitt entspricht Neutrik's bewährter D-Form, so dass eine einfache Integration in bestehende Systeme möglich ist.

Features & Benefits

- ✓ Als OEM-Equipment vorgesehener Einbausteckverbinder in gängiger D-Form-Bauweise
- ✓ Verbesserte Führungsnase für sichere und korrekte Verbindung
- ✓ Robuster Hybrid-Durchgangsadapter
 - MPO-Ausschnitt für Patch-Kabel
 - 2 Power-Kontakte
 - 1 GND-Kontakt
- ✓ Entwickelt als Durchgangsadapter für einfachen Service und Austausch
- ✓ Geschirmtes System mit EMV-Schutz
- ✓ Geeignet für medizinische Anwendungen, z. B. im OP-Saal (indoor)

Technical Information

Produkte

Title	NO16FD-XP
Gender	Female

Elektrisch

Contact resistance	< 7 mΩ
Insulation resistance	> 10 GΩ (initial)
Mains	12V AC / 10A / @50 Hz

Mechanische Daten

Insertion force	< 45 N
Withdrawal force	< 45 N
Lifetime (typ.)	10'000 mating cycles
Locking force	900 N
Locking device	Push/Pull
Mounting direction	Front mounting
Wiresize (power)	Max. 16 AWG

Material

Contacts	Brass
Insert	Polyetherimide and Polycarbonate (PEI+PC)
Shell	Zinc diecast and Polyoxmethylen
Shell plating	Nickel

Umwelt	
Flammability	UL94 V-0
Temperature range	-40°C to +75°C