



opticalCON QUAD MED Chassis

Female chassis connector, black chromium plating, front panel mount, IP65 ingress protection in mated condition with SCDP-*

The chassis connector acts as a "feed-through" allowing simplified installations by connecting four conventional LCs on the rear. It is built in the NEUTRIK standard D size shell and features an automatic sealing cover for maximum dust and dirt protection and a Push-Pull locking mechanism for safe connection.

Features & Benefits

- ✓ Suggested OEM equipment connector with common D-shape design
- ✓ Rugged 4-channel Point-to-Point multichannel routing solution
- ✓ Laser protected metal shutter seals dust proof with two-component rubber gasket
- ✓ Accommodates standard LC connectors on the rear for cost effective and simple installations
- ✓ IP65 ingress protection in mated condition with SCDP-*
- ✓ Designed as feedthrough for easy repair and replacement
- ✓ Suitable for medical Application like Operation Rooms (indoor)

Technical Information

Produkte

Title	NO4FDW-A
Gender	Female

Mechanische Daten

Insertion force	< 45N
Withdrawal force	< 45N
Lifetime	>5'000 mating cycles
Locking force	900N
Locking device	Push/Pull
Mounting direction	Front mounting

Material

Insert	Polyamide (PA 6, PBT 30 % GR, PBT 50 % GR)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Black chromium

Umwelt

Flammability	UL94 V-0
Temperature range	-40°C to +75°C