



## NA3FJ

3 pole XLR female - Stereo 1/4" locking jack (tip, ring, sleeve contact)

### Features & Benefits

- Versatile, pre-wired and ready to use adapters to reliably interlock various connector systems
- Professional look and compact space saving design, based on the XX Series
- Rugged diecast shell for best reliability

## Technical Information

Product	
<b>Title</b>	NA3FJ
<b>Connection Type</b>	Adapter

Electrical	
<b>Contact resistance</b>	$\leq 3 \text{ m}\Omega$ (XLR)
<b>Contact resistance</b>	$\leq 6 \text{ m}\Omega$
<b>Dielectric strength</b>	1.5 kV dc / > 1 kVdc (XLR/Jack)
<b>Insulation resistance</b>	> 2 G $\Omega$

Mechanical	
<b>Wire size</b>	
<b>Locking device</b>	Latch lock

Material	
<b>Contact plating</b>	2 $\mu\text{m}$ Ag
<b>Contacts</b>	Bronze (CuBe2) (jack)
<b>Insert</b>	Polyamide (PA 6.6 30 % GR)
<b>Shell</b>	Zinc diecast (ZnAl4Cu1)
<b>Shell plating</b>	gal Cu/Ni

Environmental	
<b>Temperature range</b>	-20 °C to +65 °C