



# **NAC3FPX-ST**

#### \* DISCONTINUED \*

Successor product: NAC3FPX-ST-TOP

Appliance outlet connector, screw terminals

The powerCON TRUE1 is a locking 16 A true mains connector. It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed in order to guarantee a safe power connection.

The powerCON TRUE1 is a connector with breaking capacity (CBC), i.e. it can be connected or disconnected under load or live.

### **Features & Benefits**

### **Appliance outlet**

- True mains connector with breaking capacity (CBC)
- ✓ Lockable 16 A single phase connector (USA: 20 A)
- Easy and reliable twist lock system
- Extremely robust and reliable
- ✓ ENEC certified according to IEC 60320
- UL recognized components
- ✓ IP65 ingress protection in combination with SCNAC-FPX (mated or with closed cap)

## **Technical Information**



### **Product**

Title NAC3FPX-ST

Electrical	
Contact resistance	≤ 3 mΩ
Dielectric strength	4 kVdc / 2.8 kVac
Insulation resistance	> 0.1 G $\Omega$ (after damp heat test)
Number of electrical contacts	2 + PE
Rated current per contact	16 A rms (USA: 20 A)
Rated voltage	250 V ac

Mechanical	
Lifetime	> 5000 mating cycles
Wiresize	2.5 mm²
Wiresize	14 AWG
Wiring	screw terminals

Material	
Contact plating	2 μm Ag
Locking element	Stainless steel
Shell	Polyamide (PA 6.6)
Contacts	Spring Copper (CuSn0.2)



Environmental	
Flammability	UL 94 V-0
Temperature range	- 30 °C - +80 °C