



# NC3MBY-B

\*\*\* DISCONTINUED \*\*\*

3 pole male XLR receptacle, steel retention lug, IDC-version for AWG 26-24 wires, black chrome shell, grounding: separate ground contact to mating connector shell and front panel

Same as A series with exception of a metal mounting flange featuring continuous circumferential ground contact to chassis for best EMC practice. UL recognized component.

## Features & Benefits

- ✓ Smallest XLR receptacles, highest packing density
- ✓ Metal mounting flange featuring continuous circumferential ground contact to chassis for best EMC and RF protection
- ✓ Housing flammability UL94V-0

## Technical Information

| Product         |          |
|-----------------|----------|
| Title           | NC3MBY-B |
| Connection Type | XLR      |
| Gender          | male     |

| Electrical                   |   |
|------------------------------|---|
| Capacitance between contacts | $\leq 4 \text{ pF}$                                     |
| Contact resistance           | $\leq 5 \text{ m}\Omega$                                |
| Dielectric strength          | 1,5 kVdc  |
| Insulation resistance        | $> 10 \text{ G}\Omega$ (initial)                        |
| Rated current per contact    | 6 A   |
| Rated voltage                | $< 50 \text{ V}$  |
| Grounding Options            | connector shell connected to front panel via ground lug |

| Mechanical         |                              |
|--------------------|------------------------------|
| Insertion force    | $\leq 20 \text{ N}$          |
| Withdrawal force   | $\leq 20 \text{ N}$          |
| Lifetime           | $> 1000$ mating cycles       |
| Wiresize           |                              |
| Wiring             | IDC-version for AWG 24 wires |
| Locking device     | Latch lock                   |
| Mounting direction | Rear mounting                |
| Chassis shape      | B                            |
| Mounting           | B-Screw                      |

| Material        |                            |
|-----------------|----------------------------|
| Contacts        | Brass (CuZn35Pb2)          |
| Insert          | Polyamide (PA 6.6 30 % GR) |
| Locking element | Steel Ck67                 |
| Ring            | Zinc diecast (ZnAl4Cu1)    |
| Flange          | Black Metal                |

| Environmental       |                  |
|---------------------|------------------|
| Approvals           | UL               |
| Flammability        | UL 94 V-0        |
| Standard compliance | IEC 61076-2-103  |
| Protection class    | IP 40            |
| Temperature range   | -30 °C to +80 °C |