



NL2FX

*** DISCONTINUED ***

Direct replacement / successor: NL2FXX-W-S

2 pole cable connector, chuck type strain relief

The industry-standard for loudspeaker connections offer extremely reliable and robust cable connectors with a reliable locking system. They feature solid contacts with screw-type terminals including a stranded wire protection which offer also solder termination.

Features & Benefits

- ✓ Up to 32 A rms current rating
- ✓ Only 3 parts, easy to assemble
- ✓ High impact materials – long-lasting and reliable
- ✓ Easy and extremely precise locking system "Quick Lock"
- ✓ 1 piece strain relief, chuck for 6 to 10 mm cable O.D.
- ✓ Improved grip on latch
- ✓ Mates with 4-pole chassis connector as well and makes contact with +1/-1
- ✓ Certified according to IEC61984
- ✓ Suitable for IEC62368-1 compliant devices

Technical Information

Product	
Title	NL2FX
Connection Type	speakON
Gender	female

Electrical	
Contact resistance	< 2 m Ω (after lifetime)
Dielectric strength	4 kVdc (peak)
Insulation resistance	> 1 G Ω (after dampheat)
Rated current per contact	32 A rms continuous
Rated voltage	250 V ac
Attention	This product is strictly not intended for use as an AC mains or power supply connector! CAUTION: NOT FOR INTERRUPTING CURRENT

Mechanical	
Cable O.D.	6 - 10 mm
Cable retention	\geq 220 N (subject to cable O.D. and material)
Lifetime	> 5000 mating cycles
Wiresize	1.5 - 4 mm ²
Wiresize	16 - 12 AWG
Wiring	screw type terminals or soldering
Locking device	Quick Lock (latch)

Material	
Contact plating	4 µm Ag
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 66)
Locking element	Zinc diecast (ZnAl4Cu1)
Shell	PBTP 20 % GR
Strain relief	Polyacetal (POM)

Environmental	
Flammability	UL 94 V-0
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C