



opticalCON QUAD LITE

4 channel fiber system, improved bending performance due to new tactical fiber design, black matt outer jacket, available in multi- and single-mode (PC or APC).

Besides extreme applications there is also a demand for quality fiber connections for semi-rugged applications as e.g. patching, or permanent installations. Such applications require a focus on costs and a sealing shutter is not required. The opticalCON QUAD LITE offers high performance and a cost effective, compact, and light weight design. It is fully compatible with the standard opticalCON QUAD chassis connector.

Features & Benefits


- Ruggedized 4 channel fiber optic connection system
- Cost optimized fiber connection for semi and permanent installation
- Designed for point-to-point connections
- Waterproof acc. to IP65 safety standard in mated condition
- Lightweight plastic housing
- Reliable Push-Pull locking mechanism
- Easy to clean, no special tools required
- Compatible with standard opticalCON NO4FDW-A chassis
- Custom color coding possible
- Tactical patch cable

The opticalCON QUAD LITE cable connector accommodates a standard optical 1.25 mm ferrule in a durable plastic housing. It features a spring loaded push-pull locking mechanism and an excellent cable retention utilizing aramid yarn. The connector comes pre-assembled and is not available as a single component. The cable is available in different lengths and comes with an airspool packaging.



Tactical Patch Cable

Conventional patch cables are sensitive in terms of undercutting the minimum bending radius and lateral pressure. Neutrik's tactical patch cables contain a unique fiber design including a protection layer which allows bending with minimal radius and increased lateral pressure. Therefore the tactical patch cables are the right choice for permanent or semi-permanent applications.



Technical Information

| Product | |
|-----------------|----------------------|
| Title | opticalCON QUAD LITE |
| Connection Type | opticalCON |
| Gender | male |

| Mechanical | |
|------------------|--------------------|
| Cable retention | > 250 N |
| Insertion force | < 45 N |
| Withdrawal force | < 45 N |
| Lifetime (typ.) | 2500 mating cycles |
| Wiresize | |
| Locking device | Push-Pull |

| Material | |
|---------------------|--|
| Boot | Rubber (EPDM) |
| Bushing | Polyamide (PA 6) & Thermoplastic elastomer (TPU) |
| Insert | PBT |
| Shell | PBT |
| Strain relief | CuZn36 Pb3 (Brass) |
| Dust protection cap | Rubber (EPDM) |

Environmental

| | |
|--------------------------|------------------|
| Flammability | UL94 HB |
| Temperature range | -40 °C to +70 °C |
| Optical wiring | ISO / IEC 11801 |

Optical

| | |
|----------------------------|--------------------------------------|
| Insertion loss | < 0.45 dB / connection |
| Optical connector | 1.25 mm ceramic ferrule (PC and APC) |
| Optical return loss | > 50 dB (PC) > 60 dB (APC) |

Mobile cable

| | |
|-------------------------------|-----------------------------------|
| Colour | black, matte |
| Core diameter | Single mode 9 µm, Multimode 50 µm |
| Cladding diameter | 125 µm PVC |
| minimal bending radius | 3.5 cm |
| Number of fibers | 4 |
| Cable retention | Aramid yarn |
| Weigth | 14 kg/km |
| Overall diameter | 3.5 mm |