



ORDERING CODE:

NKOP1X-LC-0-X

- cable length:[1=1m;2=2m;etc.]
- Airspool Package
- LC[UPC]
- Fibertype: S[Singlemode] or M[Multimode]
- Simplex cable
- NEUTRIK Cable opticalCON

NOTES:

- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - OM3, OM4, OM5 - IL<0.25dB , RL>30dB , 850nm&1300nm
 OS2 - IL<0.25dB, LC/APC - RL>60dB, 1310nm & 1550nm
 LC/UPC - RL>50dB, 1310nm & 1550nm
 IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B
 RL CONNECTOR VALUE ACCORDING IEC 61300-3-6
- 3 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35.
 END FACE GEOMETRY ACCORDING TO TELCORDIA GR-326
- 4 - TRACEABILITY LABEL ON THE CABLE CONTAINS SERIEL NUMBER,
 DATE OF PRODUCTION AND ASSEMBLY LENGTH

Sheet Number 1/1	Projection 	Scale 1:1	Format A3	General Tolerancing ISO 2768 mK	
Description			Created on/by	18.09.2024	Schuster R.
NKOP1X-LC-0-X			Approved on/by		
			Article ID	Model ID	Drawing ID
Status			Revision	ECN Number	
			-	-	

Neutrik Group