



Assembled Stage Box Trapezoid

Stage-box trapezoid assembled with whip or multipin

Scope the well-known Contrik stage-box trapezoid cable with modular assembly. If you need support to choose the right one according to your request, please contact us.

Choose the appropriate stagebox trapezoid:

For 8 Channels

NSB1B-8/0

Stagebox 8 inputs (F) only

Width: 117 mm, Height: 79 mm, Length: 132 mm

2-sided connector outlet

NSB1C-8/0

Stagebox 8 inputs (F) only

Width: 87 mm, Height: 77 mm, Length: 132 mm

2-sided straight connector outlet For 12 Channels

NSB1A-8/4

Stagebox 8 input (F) 4 output (M)

Width: 134 mm, Height: 79 mm, Length: 132 mm

2-sided with connector outlet above

For 16 Channels

NSB2B-16/0

Stagebox type B 16 inputs (F) only

Width: 117 mm, Height: 79 mm, Length: 252 mm

2-sided connector outlet

NSB2C-12/4

Stagebox type C 12 inputs (F)

Width: 87 mm, Height: 77 mm, Length: 252 mm

2-sided straight connector outlet

For 24 Channels

NSB3B-20/4

Stagebox type B 20 inputs (F)

Width: 117 mm, Height: 79 mm, Length: 372 mm

2-sided connector outlet

NSB3C-20/4

Stagebox type C 20 inputs (F)

Width: 87 mm, Height: 77 mm, Length: 372 mm

2-sided straight connector outlet

NSB2A-20/4

Stagebox type A 20 inputs (F)

Width: 134 mm, Height: 79 mm, Length: 252 mm

2-sided and connector outlet above

For 32 to 36 Channels

NSB3A-32/4

Stagebox type A 32 inputs (F)

To customize your panel for chassis or empty with the following plates:

NSB-4WAYPANEL - Cover plate with 4x D-cut-outs

NSB-8WAYPANEL - Cover plate with 8x D-cut-outs

NSB-4WAYBLANK - Blind panel sized for 4 chassis connectors

NSB-8WAYBLANK - Blind panel sized for 8 chassis connectors

Choose the appropriate connector panels and connectors:

XLR male - (amount)

XLR female - (amount)

Jacks 3 pole (amount)

Phono Jack (amount)

Blind cover black (amount)

Corresponding label ordering numbers:

NSBL13IN - LABEL 13-16 input

NSBL17IN - LABEL 17-20 input

NSBL1IN - LABEL 1-4 input

NSBL1OUT - LABEL 1-4 output

NSBL21IN - LABEL 21-24 input

NSBL25IN - LABEL 25-28 input

NSBL29IN - LABEL 29-32 input

NSBL5IN - LABEL 5-8 input

NSBL5OUT - LABEL 5-8 output

NSBL9IN - LABEL 9-12 input

Choose the appropriate cable for your application:

- screened analogue stranded cable for live applications with flexible PVC jacket (up-to 48 channels)

- screened digital stranded cable for live applications with flexible PVC jacket (up-to 16 channels)

Cable lengths from 5 to 50 meters

Whip lengths from 1 to 3 meters

Choose the corresponding connectors for the whip:

Multipin cable connector

Multipin female connector

For 8 Channels:

25pin

For 12 Channels:

37pin

For 16 Channels:

54pin

For 24 Channels:

72 pin

For 32 Channels:

100pin

For 36 Channels:

150pin

Declare and / or mark

Declare a channel number with coloured sleeves
(amount according to the impedance code) and/or
mark the channel number with a transparent coding
ring.

Further options

Pilo protection tube

Cable grip for better handling